



Reinforcement Notes:

- BOTTOM:** 6x6 W2.9xW2.9 (6 gage) with 3/8" rods at 12" OC each way turned 12" into sidewalls
- TOP:** 6x6, W2.9xW2.9 (6 Gage) Welded Wire Fabric with 3/8" at 12" OC each way
- SIDEWALLS:** 6x6, W1.4xW1.4 (10 gage) Welded Wire Fabric with 3/8" rods at 20" OC horizontally.
- INTERIOR WALLS:** 6x6, W1.4xW1.4 (10 Gage) Welded Wire Fabric

DESCRIPTION:
MODEL AA600W-4075

Treatment Capacity: 600 GPD			
BOD Loading: 1.50 #/DAY			
DWG REF: D-TA-xxx		REV: 0	DATE: 10/10/06
SCALE: FULL		ENG: JKC	
<p>ECOLOGICAL TANKS, INC 2247 HWY 151 NORTH DOWNSVILLE, LA 71234 318-644-0397 OFFICE 318-644-7257 FAX</p>			
<p>NO PART OF THIS DRAWING MAY BE REPRODUCED, STORED IN ANY RETRIEVAL SYSTEM, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC, MECHANICAL, PHOTOCOPIING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF ECOLOGICAL TANKS, INC.</p>			

ALL DIMENSIONS IN INCHES

