



Reinforcement Notes:

SIDES & BOTTOM: 6x6 10/10 W.W.F.
4000 PSI CONCRETE

TOP: 6x6, 10/10 W.W.F. AND
3/8" RODS 9" O.C. EACH WAY
4000 PSI CONCRETE

NOTES: START REINFORCING RODS 6"
FROM OUTSIDE EDGE OF TOP
EXTEND REINFORCING RODS TO WITHIN
1/2" OF EDGE OF TOP

ALL DIMENSIONS IN INCHES

ECOLOGICAL TANKS, INC

2247 HWY 151 NORTH
DOWNSVILLE, LA 71234
318-644-0397 OFFICE
318-644-7257 FAX

Model: ASO600C 4 + 75

PATENT PENDING

Treatment Capacity: 600 GPD

Flow Line Volume: 907 GAL.

B.O.D. Loading: 1.50#/day

NO PART OF THIS DOCUMENT MAY BE REPRODUCED,
STORED IN ANY RETRIEVAL SYSTEM, OR TRANSMITTED
IN ANY FORM OR BY ANY MEANS, ELECTRONIC,
MECHANICAL, PHOTOCOPYING, RECORDING OR
OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION
OF ECOLOGICAL TANKS, INC.

SCALE:
NTS

DATE
3/22/19

DRAWING NO.
ASO600C 4 + 75.pdf